

GROUTING MATERIALS							
		1-6 MM	FLEX 0-3 MM	FLEX 3-10 MM	POOL G 2-10 MM	RUSTIK 3-20 MM	EPOXY
TILE FORMAT	CERAMIC TILE (FOR WALLS)	●	●	●	●		
	CERAMIC TILE (FOR FLOORS)	●	●	●	●		
	PORCELAIN TILE		●	●	●		●
	GLASS TILE / MOSAIC		●				
	GRANITE TILE	●	●	●	●		●
	MARBLE & NATURAL STONE	●	●	●	●	●	
	POOL TILE				●		●
	METAL TILE						●
APPLICATION AREA	JOINT WIDTH	1-6 mm	0-3 mm	3-10 mm	2-10 mm	3-20 mm	3-15 mm
	INTERIOR (FLOORS & WALLS)	●	●	●	●	●	●
	EXTERIOR (FLOORS & WALLS)	○	●	●	●	●	●
	WET AREA & BATHROOM		●	●	●		
	KITCHEN		●	●	●	●	●
	TURKISH BATH & SAUNA		○	○	●		●
	WALK WAY & GARDEN WALLS		●	●	●	●	
	TERRACE		●	●	●	●	●
	PARKING AREA		○	○	●		●
	INDUSTRIAL AREA & FLOORS		○	○	●		●
	INDUSTRIAL KITCHEN				●		●
	SHOPPING CENTER		●	●	●		●
	HOSPITAL		●	●	●		●
	BOUTIQUE POOL		○	○	●		●
	THERMAL POOL				●		●
	SWIMMING POOL						●
	FLEXIBLE FLOORS (WOODEN & STEEL CONSTRUCTION)		●	●	●		
	LABORATORY				●		●
FOOD FACTORY						●	

● Applicable.
○ Vitra Fix LATEX performance improving additive should be added into the grouting material.